



MIXING BOWL UNLOADING STATION

Vertical trolley designed for emptying mixing bowls with diameter up to Ø 700 mm.


The machine's work cycles are managed by an electro-pneumatic panel with PLC.

The structure includes an adjustable bowl-pump centring system.

Piston pump fitted with a scraper plate shaped to the same geometry as the bottom of the bowl to ensure complete emptying.

The machine can be run by a single operator

The presence of electro-magnetic sensors guarantees the stop of the pump's stroke once the bowl has been emptied and its return on top position.



SIZES

Three available sizes:

With PA65AM pump for flow rates up to 24 l/min.

With PA80AM pump for flow rates up to 33 l/min.

With PA100AM pump for flow rates up to 52 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.
- FDA Blu scraper plate gasket.

Possibility to manage the emptying cycle in remote mode.

LARGE MIXING BOWL UNLOADING STATION

Structure designed for emptying mixing bowls with diameter exceeding Ø 700 mm.

The machine's work cycles are managed by an electro-pneumatic panel with PLC.

Movement of the pump is controlled by two pneumatic cylinders to guarantee equal distribution of the thrust over the extended surface of the plate.

The structure includes an adjustable bowl-pump centring system.

Piston pump fitted with a scraper plate shaped to the same geometry as the bottom of the bowl to ensure complete emptying.

The machine can be run by a single operator

The presence of electro-magnetic sensors guarantees the stop of the pump's stroke once the bowl has been emptied and its return on top position.



SIZES

Two available sizes:

With PA100AM pump for flow rates up to 52 l/min.

With PA140AM pump for flow rates up to 95 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinders.
- FDA Blu scraper plate gasket.

Possibility to manage the emptying cycle in remote mode.



DRUM UNLOADING STATION

C.S.F. Inox S.p.a. offers a wide range of drum unloading stations for any production need. Versatile and flexible, this range features piston-type drum unloading machines available in various sizes and with varying equipment, made with top-quality electro-pneumatic components. The whole series is made with a fully AISI 304 stainless steel structure.

Thanks to the use of pneumatic piston pumps, CSF drum unloading machines can handle a multitude of products, from low viscosities to values over 100,000 cP.



Numerous pumpable food products: creams, sauces, tomato concentrate, fruit purées, chocolate, pastry creams and batters, jams, ragout, yoghurt, melted cheese and beverages, such as syrups, glucose, concentrates, juices.

Can also be used in the cosmetic sector to pump products such as solutions, beauty creams and shaving creams.



DRUM UNLOADING STATION FOR IMMERSED PUMP

Wheel-mounted pneumatic station suitable for emptying conical and cylindrical drums with diameter up to Ø 700 mm and height up to 1,000 mm. Structure designed for use with the long version piston pump with the inlet immersed and no scraper plate. It is suitable for handling low viscosity liquids. Complete with pneumatic control panel for quick and easy control of pump movement.

The machine can be run by a single operator

SIZES

- Four available sizes:
- With PA65AM pump for flow rates up to 24 l/min.
- With PA80AM pump for flow rates up to 33 l/min.
- With PA100AM pump for flow rates up to 52 l/min.
- With PA140AM pump for flow rates up to 100 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.

DRUM UNLOADING STATION WITH SCRAPER PLATE

Drum unloading station suitable for emptying conical and cylindrical drums with diameter up to Ø 700 mm and height up to 1,000 mm. The machine cycles are managed by an electro-pneumatic panel with PLC. The presence of electro-magnetic sensors guarantees the stop of the pump once the drum has been emptied and its return on top position. The pump is equipped with a scraper plate to guarantee complete emptying of the drum.

The structure includes an adjustable drum-pump centring system. Suitable for high viscosity products such as double-ripe tomato concentrate and fruit purées.

The machine can be run by a single operator.

N.B.: Drums don't need any fixing system.

SIZES

- Four available sizes:
- With PA65AM pump for flow rates up to 24 l/min.
- With PA80AM pump for flow rates up to 33 l/min.
- With PA100AM pump for flow rates up to 52 l/min.
- With PA140AM pump for flow rates up to 100 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.
- FDA Btu trace-free seal.
- Possibility to manage the emptying cycle in remote mode.



DRUM UNLOADING STATION WITH DUAL-ARTICULATION ARM

Pneumatic station with dual-articulation arm suitable for conical and cylindrical drums up to Ø 700 mm and height up to 1,000 mm. The machine's work cycles are managed by an electro-pneumatic panel with PLC.


The machine is equipped with a scraper plate to guarantee optimal emptying of the drums. The presence of electro-pneumatic sensors guarantees the stop of the pump's stroke once the drum has been emptied and its return on top position.

It can empty groups of 4 - 8 drums positioned on pallets.

The machine can be run by a single operator

Ideal for high viscosity products such as double-ripe tomato concentrate and fruit purées.

N.B.: Drums don't need any fixing system.



SMALL-BUCKET UNLOADING STATION

Wheel-mounted pneumatic station suitable for handling small buckets. The machine's work cycles are managed by an electro-pneumatic panel with PLC. The presence of electro-magnetic sensors guarantees the stop of the pump's stroke once the bucket has been emptied and its return on top position. Ideal for high viscosity products such as chocolate, confectioner's creams, dairy products and jam.

Correct positioning of the bucket is guaranteed by a locking system incorporated in the structure.

SIZES

- Three available sizes:
- With PA50AM pump for flow rates up to 10,6 l/min.
- With PA65AM pump for flow rates up to 24 l/min.
- With PA80AM pump for flow rates up to 33 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.
- FDA Btu seal.
- Possibility to manage the emptying cycle in remote mode.



DRUM UNLOADING STATION WITH TURNABLE

Pneumatic station with turntable, suitable for emptying four drums with diameter up to Ø 700 mm and height up to 1,000 mm.

Structure designed for use with the long version piston pump, with immersed inlet.

The turntable installed at the base of the structure, can rotate 4 drums so that they can be positioned under the pump in quick succession. Complete with pneumatic control panel for quick and easy control of pump movement.

The machine can be run by a single operator


SIZES

- Two available sizes:
- With PA100AM pump for flow rates up to 52 l/min.
- With PA140AM pump for flow rates up to 95 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.



8 DRUM EMPTYING SET-UP



SIZES

- Three available sizes:
- With PA80AM pump for flow rates up to 33 l/min.
- With PA100AM pump for flow rates up to 52 l/min.
- With PA140AM pump for flow rates up to 100 l/min.

N.B.: Flow rates refer to products with a viscosity of 1,000 cP

OPTIONAL

- HCR (High corrosion resistance) pneumatic cylinder.
- FDA Btu scraper plate gasket.
- Support base.

