



A-PF Solutions s.r.l.

S + 32 (0)478 29 26 69

🖂 info@apfs.be

www.apfs.be

We strongly believe in innovation, always aware that in the field of thermal exchange new materials and process technologies may arise. We want to be an active player in this direction. We only aim for excellence, with the courage to admit mistakes and changing.

MBS STRENGTH

INNOVATION

Since its beginning, MBS has believed in the importance of research and development of new technology that delivers value and worth for the customer.

QUALITY AND KNOWLEDGE

Thanks to the skilled workmanship and the expertise of its team, MBS offers high-quality products.


CUSTOMER'S SATISFACTION


MBS aims to meet the customers' needs by offering technical and commercial support to ensure customized solutions in line with key industry regulations.

PRODUCTION EFFICIENCY

MBS has introduced a LEAN production system for several years now with a view to continuous production improvement.

Our history





CSFinoxGroup

FLOW TECHNOLOGY COMPONENTS

Joining CSF's GROUP, MBS starts its expansion and entry into international markets.

CSF Inox Group aims to produce and sell components (Pumps, Valves, Heat Exchangers) to the hygienic and sanitary industry sectors such as: Food, Beverage, Cosmetic, Pharmaceutical and Bio-Technologies.







EMBS















\sim food and \sim beverage \sim

----- PHARMA ----

Corrugated Tubular Heat Exchanger

Corrugation is the process of creating an internal corrugated surface inside smooth tubes, which allows a higher flow turbulence, improving the heat exchange efficiency.

The MBS Heat Exchanger sizing is carried out through a sophisticated calculation software, constantly improved and updated thanks to the decennial co-operation with Parma's University (Technical Physics Department)





~~~ INDUSTRIAL ~~~~

# 

### Plus

- Reduction of the required areas
- Contact times and product's permanence reduction inside the item
- Reduced washing times due to a higher mechanical action generated by turbulence
- Vertical or horizontal installation
- Ability to work with high pressures and temperatures
- Minimum maintenance cost due to gasket-free design
- Ease of assembly and modularity of the exchanger

# FOOD & BEVERAGE~~~~

MBS Heat Exchangers range is designed and manufactured for the Food industry according to the strictest hygienic standards. Suitable for processing high and medium viscosity products such as milk, juices, nectars and fruit puree, wine, beer, cream, ice cream etc. MLW version is EHEDG and 3A certified.

### STANDARD TECHNICAL FEATURES

Material Product side.AISI 316L(other materials supplied on request)Finishing Product side.Ra < 0,8 μm</td>Pressure Project.10 barMax temperature project.





### SANITARY MIXFLO MONOTUBE MNW SERIE

Monotube mixflo Heat Exchanger consists in two concentric corrugated tubes.

The product to be thermally treated flows inside the smaller tube while service fluid flows into external jacket.

Particularly suitable for products having a medium or high viscosity even with particulates in suspension such as pressed grapes, fruit and vegetables concentrate.

#### SANITARY MIXFLO MULTITUBE MLW SERIE

Multitube mixflo Heat Exchanger consists of small corrugated tubes inside a shell welded from one end to the other. An expansion joint is fitted on the external shell.

Particularly suitable for products having a medium or low viscosity even with pulps and fiber, small particulates such as milk, juices, nectar, cream, sugar solutions etc.

### FOOD & BEVERAGE





### MULTITUBE MIXFLO DISASSEMBLED

Manufactured with small corrugated tubes placed inside the shell. The tube bundle can be removed from the shell. It is not equipped with expansion joint due to floating plates.

**Particularly suitable for products** having a **medium or low viscosity** even with pulps, fiber, small particulates such as **milk, juices, nectar, cream, sugar solutions etc.** 

### MIXFLO SANITARY ANULAR SPACE SERIE

Manufactured with 3 or 4 corrugated concentric tubes. Product side can be examined. Installed expansion joint on the external shell.

**Particularly suitable for products** having a **medium or high viscosity** even with particulates such as **fruit or vegetable concentrates**, ketchup etc.





# 


MBS Heat Exchangers range is designed and manufactured for the pharmaceutical industry according to the strictest hygienic standards Particularly suitable for products having a low viscosity such as: injectable water, ethanol, protein solutions etc.

MLP version is EHEDG and 3A certified

### STANDARD TECHNICAL FEATURES

| Material Product sideA                | ISI 316L |
|---------------------------------------|----------|
| (other materials supplied on request) |          |
| Finishing Product sideRa <            | < 0,8 μm |
| Ra < 0,5 µm electro p                 | olished  |
| Pressure Project                      | 10 bar   |
| Max temperature project               | 184°C    |





### MLP MULTITUBE

Manufactured to meet pharmaceutical industry standards of **hygienic and safety demands**.

PHARMAFLO Heat Exchanger consists of small diameter corrugated tubes inside a shell with plates on both ends.

With this design all kind of contamination between sterile product and service fluid is avoided.

Particularly suitable for products having a medium or low viscosity such as wfi, point of use cooling, wfi heating, condensation, protein solution etc.

### PHARMA





# INDUSTRIAL ------

MBS Heat Exchangers range is designed and manufactured for the industrial field according to the highest construction standards. Particularly suitable for CIP, combustion gases, process water, biogas, oils etc.

### STANDARD TECHNICAL FEATURES

Material Product side......AISI 316L (other materials supplied on request) Finishing Product side.....Brushed Pressure Project.....10 bar Max temperature project.....184°C



### CROSSFLO INDUSTRIAL MULTITUBE MLI SERIE

Manufactured with small corrugated tubes placed inside the shell welded from one end to the other. An Expansion joint is fitted on the external shell.

Particularly suitable for products having a medium or low viscosity such as water, cip, oils, gases, combustion gases etc.

#### MULTIFLO INDUSTRIAL MULTITUBE MULTIPASSAGING MLM SERIE

Manufactured with small corrugated tubes placed inside the shell welded from one end to the other.

The MULTIFLO exchanger is multi-passaging and the exchange is as result of the special headboards.

Particularly suitable for products having a medium or low viscosity such as water, cip, oils.



## INDUSTRIAL



### MULTIFLO U TUBES MLU INDUSTRIAL

The MULTIFLO U can be disassembled and "U" shaped the tube bundle inside the shell is easily removable for any maintenance.

Particularly suitable for products having a medium or low viscosity such as water, cip, oils.





## SCRAPED------SURFACE HEAT EXCHANGER

### Hercules


For the Hercules project, we worked closely with Parma University by means of extensive research to develop better heat exchange parameters, power absorptions and materials studies in presence of the tested products.



### HERCULES

Particularly suitable for products having high viscosity, with particulates in suspension and the tendency to adhere to the exchange surfaces, in order to turn the process from "batch" into "continuous".


Products such as: jams, ketchup, mayonnaise, soups, dressings, chocolate, meat sauces, gelatins, baby food, honey, butter, curds, ice cream, oils, fats.




### SCRAPED SURFACE



|       |      | DIMENSION (mm) |      |                     |                                  |         |                          |                       |      | PRODUCT  |          | SERVICE  |          | H30-H45 |     |   |
|-------|------|----------------|------|---------------------|----------------------------------|---------|--------------------------|-----------------------|------|----------|----------|----------|----------|---------|-----|---|
| Model | Α    | в              | с    | Exchange<br>Surface | D                                | E       | F                        | G                     | н    | P<br>MAX | T<br>MAX | P<br>MAX | T<br>MAX |         |     |   |
| H5    | 1000 | 840            | 1082 | 0,5 m²              | DIN 11851<br>DN 65 F<br>CLAMP 3" | DN 65 F | EN 1002 1                |                       | 2350 |          |          |          |          |         | Q   |   |
| H10   | 2000 | 1840           | 2082 | 1 m <sup>2</sup>    |                                  |         | DN 65 F                  | EN 1092-1<br>DN 50    | 400  | 3350     | 482      | 19,5     | 184      | 10      | 184 |   |
| H15   | 3000 | 2840           | 3082 | 1,5 m²              |                                  |         |                          | PN 16                 |      | 4350     |          |          |          |         |     |   |
| H30   | 1370 | 1138           | 1503 | 3,2 m <sup>2</sup>  | DIN 11864-2<br>2" 1/2            |         | DIN 11864-2<br>2" 1/2 DN | DIN 11864-2 EN 1092-1 | 050  | 2517     | 15 1     | 100      | 8        | 172     |     |   |
| H45   | 1900 | 1666           | 2031 | 4,5 m <sup>2</sup>  |                                  |         |                          | DN 40/32<br>PN 16     | 950  | 1500     | 3045     | 15       | 160      | ð       | 172 | C |





G

## RESEARCH AND DEVELOPEMENT

#### Certificates

The following certificates acquired by MBS are showing our compromise to a constant improvement both operational and industrial. All the exchangers are compliant with PED 2014/68/UE.











Standard Number 12 - 07

### Co-operation

#### MBS has cooperated from more than 25 years with Parma University. Thanks to this co-operation, in particular with Technical Physics, we developed our products on an adequate scientific basis.









CSFinoxGroup

FLOW TECHNOLOGY COMPONENTS